

## Statement of Verification

BREG EN EPD No.: 000505

Issue 01

This is to verify that the

### Environmental Product Declaration

provided by:

**PPG Architectural Coatings UK Ltd**

is in accordance with the requirements of:

**EN 15804:2012+A2:2019**

and

**BRE Global Scheme Document SD207**

This declaration is for:

**1m<sup>2</sup> of Johnstone's Trade UltraLast Matt**



### Company Address

PPG Industries UK Ltd.  
Needham Rd  
Stowmarket IP14 2AD,  
United Kingdom



Signed for BRE Global Ltd

Emma Baker

Operator

09 June 2023

Date of this Issue

09 June 2023

Date of First Issue

08 June 2028

Expiry Date



This Statement of Verification is issued subject to terms and conditions (for details visit [www.greenbooklive.com/terms](http://www.greenbooklive.com/terms)).

To check the validity of this statement of verification please, visit [www.greenbooklive.com/check](http://www.greenbooklive.com/check) or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [Enquiries@breglobal.com](mailto:Enquiries@breglobal.com)



## Environmental Product Declaration

EPD Number: 000505

### General Information

EPD Programme Operator	Applicable Product Category Rules
BRE Global Watford, Herts WD25 9XX United Kingdom	BRE Environmental Profiles 2013 Product Category Rules for Type III environmental product declaration of construction products to EN 15804+A2 PN 514 Rev 3.0
Commissioner of LCA study	LCA consultant/Tool
PPG Architectural Coatings UK Ltd. Huddersfield Road Birstall - Batley, West Yorkshire WF17 9XA United Kingdom	William Collinge LCA Analyst PPG Monroeville Business and Technology Center 440 College Park Drive Monroeville , PA 15146 USA
Declared/Functional Unit	Applicability/Coverage
Protecting and decorating 1m <sup>2</sup> of substrate, suitably prepared, on the basis of two layers of the product.	Product Average.
EPD Type	Background database
Cradle to Gate with options	ecoinvent, Industry Data 2.0
Demonstration of Verification	
CEN standard EN 15804 serves as the core PCR <sup>a</sup>	
Independent verification of the declaration and data according to EN ISO 14025:2010 <input type="checkbox"/> Internal <input checked="" type="checkbox"/> External	
(Where appropriate <sup>b</sup> )Third party verifier: Pat Hermon	
a: Product category rules b: Optional for business-to-business communication; mandatory for business-to-consumer communication (see EN ISO 14025:2010, 9.4)	
Comparability	
Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A2:2019. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A2:2019 for further guidance	

## Information modules covered

Product			Construction		Use stage							End-of-life				Benefits and loads beyond the system boundary
A1	A2	A3	A4	A5	Related to the building fabric					Related to the building		C1	C2	C3	C4	D
Raw materials supply	Transport	Manufacturing	Transport to site	Construction – Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, Recovery and/or Recycling potential
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Note: Ticks indicate the Information Modules declared.

## Manufacturing site(s)

PPG Coatings Nederland B.V.  
 Oceanenweg 2  
 1047 BB Amsterdam  
 Netherlands

## Construction Product:

### Product Description

Johnstone’s Trade UltraLast Matt is a premium quality scuff resilient, matt wall paint that is stain resistant and can be easily cleaned without polishing. The scuff resilience makes it long lasting and perfectly suited for high footfall areas, commercial environments, and public buildings. The low emission levels mean that UltraLast Matt has a reduced impact on indoor air quality.

One EPD is produced per product group. In order to group different color bases belonging to the same product type (if applicable) within each EPD, the color base with the worst case (highest) GWP was selected.

EPD	Product Name
Johnstone’s Trade Ultralast Matt	Johnstone’s Trade Ultralast Matt

Technical Information

	Property	Value, Unit
Johnstone's Trade Ultralast Matt	Spreading rate	11 m <sup>2</sup> /L
	Time to Touch Dry	2 hrs
	Time to Recoat	12 hrs
	Initial coats	2
	Density	1.37 Kg/L
	Amount per declared unit	0.25 Kg/m <sup>2</sup>




### Main Product Contents

Material/Chemical Input	%
Additives	<5%
Biocides	<0.1%
Binders	20-30%
Fillers	10-20%
Glycols, esters and ethers	<0.1%
Pigments	<0.1%
Solvents	<0.1%
TiO2	10-20%
Water	30-40%

### Manufacturing Process

The manufacturing process involves the mixing and dispersing of raw materials into a homogeneous mixture. The product is then packaged for distribution to the customer.

### Process flow diagram



### Construction Installation

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone’s Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Stir well before use. Easy to apply by brush or roller. Do not apply in temperatures below 10°C.

### Use Information

No activities are required during the use phase.

## End of Life

Coatings are often not removed from their substrate, so the end of life the product is that of the end of life of the underlying substrate. After its disposal, it is assumed that the dried paint film ends up entirely in a landfill, in line with the PEFCR for decorative paints (v1.).

Benefits and loads beyond the product system boundary are reported as additional information in module D. The module declares net benefits and loads from net flows leaving the product system that have passed the end-of-waste state, except those which have been allocated as co-products. Net impacts in module D are calculated according to Annex D of EN15804+A2. It is assumed that zero kg of product is recycled, recovered for recycling or re-use, and recovered for energy.

## Life Cycle Assessment Calculation Rules

### Declared / Functional unit description

Johnstone's Trade Ultralast Matt to protect and decorate 1m<sup>2</sup> of substrate, suitably prepared, on the basis of two layers of paint at a spreading rate of 11 m<sup>2</sup>/L and a weight of 0.25 kg/m<sup>2</sup>. These characteristics apply for the paint application on interior and exterior wall surfaces.

### System boundary

The system boundaries of the product LCA follow the modular design defined by /EN15804/. This cradle-to-gate with options study includes the Product stage (A1-A3), Transport Stage (A4), Installation Stage (A5), Deconstruction/Demolition (C1), End-of-life transport (C2), Waste Processing (C3), Disposal (C4), and Reuse, recovery and/or recycling potential (D).

### Data sources, quality and allocation

Formulation is based on the current recipe extracted from PPG recipe systems. Data related to in-house PPG manufacturing processes has been collected from PPG reporting systems for the 2021 calendar year. This is based on recorded utility use and waste disposal and is of high quality.

For life cycle modelling of the process, SimaPro V.9.4 is used. All relevant background datasets are taken from Ecoinvent V3.8 database and the Industry 2.0 database supplied with SimaPro. Industry 2.0 processes are only used for raw materials.

Many Ecoinvent processes, such as waste disposal, are multi-input and not just for the material specified. For these processes the allocation used for the material in question is the one specified in the Ecoinvent process. Allocation of waste to reuse and waste disposal streams is made on the basis of recent data from reliable sources.

### Cut-off criteria

Cut off criteria are: 1% of the renewable and non-renewable energy usage or 1% of the mass of the process under consideration. The total neglected flows shall be no more than: 5% of the energy usage 5% of the total mass. Exceptions are if flows have significant effects of or energy use in their extraction, use or disposal, or are classed as hazardous waste, then these are specifically included.

## LCA Results

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			GWP-total	GWP-fossil	GWP-biogenic	GWP-luluc	ODP	AP	EP-freshwater
			kg CO2 eq	kg CO2 eq	kg CO2 eq	kg CO2 eq	kg CFC11 eq	mol H+ eq	kg (PO4)3- eq
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	4.54E-01	4.78E-01	1.48E-03	2.62E-04	4.99E-08	3.94E-03	1.53E-05
	Total (Residual+GO)	A1-3	NA	NA	NA	NA	NA	NA	NA
Construction process stage	Transport	A4	2.20E-02	2.20E-02	8.78E-06	8.63E-06	5.09E-09	8.92E-05	1.54E-07
	Construction	A5	8.52E-02	8.51E-02	3.38E-04	5.51E-05	6.08E-09	2.75E-04	2.30E-06
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
<b>100% Incineration Scenario</b>									
End of life	Deconstruction, demolition	C1	4.55E-05	4.55E-05	1.08E-08	5.67E-09	9.68E-12	4.61E-07	2.30E-10
	Transport	C2	7.44E-04	7.43E-04	2.97E-07	2.92E-07	1.72E-10	3.02E-06	5.21E-09
	Waste processing	C3	MND	MND	MND	MND	MND	MND	MND
	Disposal	C4	1.78E-02	1.78E-02	6.23E-06	1.61E-06	4.77E-10	1.33E-05	2.52E-08
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

GWP-total = Global warming potential, total;  
 GWP-fossil = Global warming potential, fossil;  
 GWP-biogenic = Global warming potential, biogenic;  
 GWP-luluc = Global warming potential, land use and land use change;

ODP = Depletion potential of the stratospheric ozone layer;  
 AP = Acidification potential, accumulated exceedance; and  
 EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment

## LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			EP-marine	EP-terrestrial	POCP	ADP-mineral&metals	ADP-fossil	WDP	PM
			kg N eq	mol N eq	kg NMVOC eq	kg Sb eq	MJ, net calorific value	m <sup>3</sup> world eq deprived	disease incidence
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	4.04E-04	4.11E-03	1.56E-03	3.50E-06	9.07E+00	3.22E-01	2.50E-08
	Total (Residual+GO)	A1-3	NA	NA	NA	NA	NA	NA	NA
Construction process stage	Transport	A4	2.66E-05	2.94E-04	8.99E-05	7.68E-08	3.32E-01	9.95E-04	1.89E-09
	Construction	A5	5.32E-05	4.96E-04	2.57E-04	2.97E-07	1.53E+00	4.04E-02	2.43E-09
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
<b>100% Incineration Scenario</b>									
End of life	Deconstruction, demolition	C1	2.02E-07	2.21E-06	6.11E-07	3.35E-11	6.21E-04	1.31E-06	1.23E-11
	Transport	C2	8.99E-07	9.93E-06	3.04E-06	2.60E-09	1.12E-02	3.36E-05	6.39E-11
	Waste processing	C3	MND	MND	MND	MND	MND	MND	MND
	Disposal	C4	4.52E-06	4.98E-05	1.82E-05	5.32E-09	3.70E-02	1.61E-03	2.64E-10
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment;  
 EP-terrestrial = Eutrophication potential, accumulated exceedance;  
 POCP = Formation potential of tropospheric ozone;  
 ADP-mineral&metals = Abiotic depletion potential for non-fossil resources;

ADP-fossil = Depletion potential of the stratospheric ozone layer;  
 WDP = Water (user) deprivation potential, deprivation-weighted water consumption; and  
 PM = Particulate matter.



## LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			IRP	ETP-fw	HTP-c	HTP-nc	SQP
			kBq U235 eq	CTUe	CTUh	CTUh	dimensionless
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	3.04E-02	1.12E+01	7.12E-10	1.49E-08	4.52E+00
	Total (Residual+GO)	A1-3	NA	NA	NA	NA	NA
Construction process stage	Transport	A4	1.44E-03	2.59E-01	8.40E-12	2.72E-10	2.28E-01
	Construction	A5	2.93E-03	9.79E-01	5.84E-11	6.77E-10	2.48E-01
Use stage	Use	B1	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND
<b>100% Incineration Scenario</b>							
End of life	Deconstruction, demolition	C1	2.59E-06	4.01E-04	2.31E-14	2.95E-13	8.32E-05
	Transport	C2	4.88E-05	8.77E-03	2.84E-13	9.19E-12	7.72E-03
	Waste processing	C3	MND	MND	MND	MND	MND
	Disposal	C4	1.46E-04	2.98E-02	2.12E-12	2.37E-11	8.83E-02
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

IRP = Potential human exposure efficiency relative to U235;  
ETP-fw = Potential comparative toxic unit for ecosystems;  
HTP-c = Potential comparative toxic unit for humans;

HTP-nc = Potential comparative toxic unit for humans; and  
SQP = Potential soil quality index.

## LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing resource use, primary energy			PERE	PERM	PERT	PENRE	PENRM	PENRT
			MJ	MJ	MJ	MJ	MJ	MJ
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	4.45E-01	1.80E-01	6.25E-01	7.15E+00	1.90E+00	9.05E+00
	Total (Residual+GO)	A1-3	NA	NA	NA	NA	NA	NA
Construction process stage	Transport	A4	4.68E-03	0.00E+00	4.68E-03	3.32E-01	0.00E+00	3.32E-01
	Construction	A5	2.52E-01	-1.80E-01	7.15E-02	1.85E+00	-3.25E-01	1.52E+00
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
<b>100% Incineration Scenario</b>								
End of life	Deconstruction, demolition	C1	5.18E-06	0.00E+00	5.18E-06	6.20E-04	0.00E+00	6.20E-04
	Transport	C2	1.58E-04	0.00E+00	1.58E-04	1.12E-02	0.00E+00	1.12E-02
	Waste processing	C3	MND	MND	MND	MND	MND	MND
	Disposal	C4	6.64E-04	0.00E+00	6.64E-04	3.70E-02	0.00E+00	3.70E-02
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;  
 PERM = Use of renewable primary energy resources used as raw materials;  
 PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;  
 PENRM = Use of non-renewable primary energy resources used as raw materials;  
 PENRT = Total use of non-renewable primary energy resource

## LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing resource use, secondary materials and fuels, use of water						
			SM	RSF	NRSF	FW
			kg	MJ net calorific value	MJ net calorific value	m3
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	0.00E+00	0.00E+00	-1.02E-02	7.81E-03
	Total (Residual+GO)	A1-3	NA	NA	NA	NA
Construction process stage	Transport	A4	0.00E+00	0.00E+00	0.00E+00	3.64E-05
	Construction	A5	0.00E+00	0.00E+00	-1.04E-04	9.12E-04
Use stage	Use	B1	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND
<b>100% Incineration Scenario</b>						
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	4.41E-08
	Transport	C2	0.00E+00	0.00E+00	0.00E+00	1.23E-06
	Waste processing	C3	MND	MND	MND	MND
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	3.88E-05
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00

SM = Use of secondary material;  
RSF = Use of renewable secondary fuels;

NRSF = Use of non-renewable secondary fuels;  
FW = Net use of fresh water

## LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Other environmental information describing waste categories					
			HWD	NHWD	RWD
			kg	kg	kg
Product stage	Raw material supply	A1	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	7.59E-02	2.44E+00	4.99E-05
	Total (Residual+GO)	A1-3	NA	NA	NA
Construction process stage	Transport	A4	2.40E-04	1.90E-02	2.25E-06
	Construction	A5	1.69E-02	3.99E-02	3.22E-06
Use stage	Use	B1	MND	MND	MND
	Maintenance	B2	MND	MND	MND
	Repair	B3	MND	MND	MND
	Replacement	B4	MND	MND	MND
	Refurbishment	B5	MND	MND	MND
	Operational energy use	B6	MND	MND	MND
	Operational water use	B7	MND	MND	MND
<b>100% Incineration Scenario</b>					
End of life	Deconstruction, demolition	C1	8.25E-07	3.85E-06	4.15E-09
	Transport	C2	8.12E-06	6.42E-04	7.60E-08
	Waste processing	C3	MND	MND	MND
	Disposal	C4	5.10E-05	1.50E-01	2.22E-07
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00

HWD = Hazardous waste disposed;  
 NHWD = Non-hazardous waste disposed;  
 RWD = Radioactive waste disposed

## LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Other environmental information describing output flows – at end of life								
			CRU	MFR	MER	EE	Biogenic carbon (product)	Biogenic carbon (packaging)
			kg	kg	kg	MJ per energy carrier	kg C	kg C
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	0.00E+00	5.52E-07	0.00E+00	0.00E+00	0.00E+00	2.37E-03
	Total (Residual+GO)	A1-3	NA	NA	NA	NA	NA	NA
Construction process stage	Transport	A4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Construction	A5	0.00E+00	3.14E-03	0.00E+00	9.16E-02	0.00E+00	-2.37E-03
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
<b>100% Incineration Scenario</b>								
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Waste processing	C3	MND	MND	MND	MND	MND	MND
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

CRU = Components for reuse;  
MFR = Materials for recycling

MER = Materials for energy recovery;  
EE = Exported Energy

## Scenarios and additional technical information

Scenarios and additional technical information			
Scenario	Parameter	Units	Results
A4 – Transport to the building site	Transport to the construction site is assumed to occur by heavy duty lorry.		
	Transport by lorry	tkm	Lorry 16-32 tonne EURO5
	Distance:	km	300
	Capacity utilisation (incl. empty returns)	%	50
	Bulk density of transported products	kg/m <sup>3</sup>	1250
A5 – Installation in the building	<p>The coating is applied to the interior wall surface using a roller. The area coated is considered 50 m<sup>2</sup>. One disposable plastic sheet is used to protect the floor from drops and spills for the entire job. After application the roller and plastic sheeting will be disposed of. Based on the practice of professional painters where as much paint removed from the cans as possible studies show 1% of the paint is lost through spills and residual paint in the can. For projects where there is a higher proportion of paint waste through higher levels of spills or residual paint left after the job, this will increase the environmental impact accordingly.</p> <p>The scenario above allows for the calculation of impact for the tools and ancillaries for the job related to the declared unit, however for the product related aspects it is assumed the paint is completely used before disposal of the packaging. All values are related to the declared unit.</p>		
	Roller for application	kg	1.23E-02
	Polyethylene sheeting for spill protection	kg	9.20E-04
	Amount of paint lost during application due drips splashes, and residue in the can/bucket	%	1
	Disposal of steel (From primary packaging. Assume 29% landfill, 71% incineration)	kg	0
	Disposal of polyethylene (From pallet packaging, spill sheeting and roller packaging. Assume 29% landfill, 71% incineration)	kg	1.36E-03
	Disposal of polypropylene (From primary packaging, roller components and roller tray. Assume 29% landfill, 71% incineration)	kg	1.88E-02
	Disposal of wood (From pallet. Assume 31% recycling, 48% incineration and 20% landfill)	kg	9.25E-03
	Disposal of paper (From pallet interleaves and roller packaging. Assume 79% recycling, 14.8% incineration and 6.2% landfill)	kg	4.02E-04
	Disposal of miscellaneous plastic waste (From roller. Assume 29% landfill, 71% incineration)	kg	1.09E-03
	VOC Emitted	kg	7.30E-05
Reference service life	The service life is highly dependent on the environment in which the product is installed. Hence the EPD gives values for the first application of the coating for the lifetime applicable to the coating in the environment in which it is used.		
C1 to C4 End of life,	Product is demolished with the building on which it is applied and then transported to disposal. The disposal occurs by incineration (100%). No credit is claimed for energy recovery.		
	Transport distance to incineration/landfill	km	30
	Amount disposed at end of life	kg	1.50E-01
Module D	No benefits or loads beyond the system boundary were found.		
	Recycled content of product kg	kg	0
	Recovered for recycling kg	kg	0
	Recovered for re-use kg	kg	0
	Recovered for energy kg	kg	0

## Summary, comments and additional information

### Interpretation

The results of the LCIA indicate which life cycle stage contributes the most to a specific environmental impact.

Analysis of the results shows that most of the impact comes from the raw materials stage (A1) for most of the impact categories. This high contribution of raw materials to the impact indicators is not unexpected. As paints are at the end of the chemical value chain much of the expenditure of energy, raw materials, processing, waste processing, etc. in bringing the product to existence has occurred prior to the entry of the raw materials onto the PPG production site. For climate change, total the contribution is divided between application (A5) and raw materials (A1).

In impact category Photochemical ozone formation, human health the highest impact occurs in stage application (A5). This can be caused by the direct VOC emissions.

## References

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A1:2013. London, BSI, 2013.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.