

Statement of Verification

BREG EN EPD No.: 000681 Issue 01

This is to verify that the

Environmental Product Declaration provided by:

HEMPEL A/S

is in accordance with the requirements of:

EN 15804:2012+A2:2019

BRE Global Scheme Document SD207

This declaration is for:

1 kilogram of Hempatop Finish 730 coating

Company Address

HEMPEL A/S Lundtoftegårdsvej 91 DK-2800 Kgs. Lyngby Denmark



Mayley Thu Signed for BRE Global Hayley Thomson

25 March 2025 Date of First Issue

24 March 2030

25 March 2025

Expiry Date

BRE/Global

This Statement of Verification is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms.

To check the validity of this statement of verification please, visit www.greenbooklive.com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.

T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com







Environmental Product Declaration

EPD Number: 000681

General Information

EPD Programme Operator	Applicable Product Category Rules								
BRE Global Watford, Herts WD25 9XX United Kingdom	BRE Environmental Profiles 2023 Product Category Rules for Type III environmental product declaration of construction products to EN 15804+A2 PN 514 Rev 3.1.								
Commissioner of LCA study	LCA consultant/Tool								
HEMPEL A/S Lundtoftegårdsvej 91 DK-2800 Kgs. Lyngby Denmark	ITeC - The Catalonia Institute of Construction Technology Wellington 19 - ES08018 Barcelona - Tel +34 933 093 404 www.itec.cat								
	SimaPro Version 9.1.1 by PRé Sustainability BV.								
Declared/Functional Unit	Applicability/Coverage								
1 kilogram of Hempatop Finish 730 coating	Product Specific								
EPD Type	Background database								
Cradle to Gate with Modules C and D	Ecoinvent v3.6 (2019) database CEPE Raw Material database v3.0								
Demonstra	ation of Verification								
CEN standard EN 15	5804 serves as the core PCR ^a								
Independent verification of the declara	ation and data according to EN ISO 14025:2010 ⊠ External								
	(Where appropriate ^b)Third party verifier: Pat Hermon								
a: Product category rules b: Optional for business-to-business communication; mandatory	for business-to-consumer communication (see EN ISO 14025:2010, 9.4)								

Comparability

Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A2:2019. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A2:2019 for further guidance



Information modules covered

	Produc	.+	Const	ruction		Use stage						End-of-life				Benefits and loads beyond
	Product			Construction		Related to the building fabric				ted to uilding	Ena-or-life				the system boundary	
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	В6	B7	C1	C2	C3	C4	D
Raw materials supply	Transport	Manufacturing	Transport to site	Construction – Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, Recovery and/or Recycling potential
V	\square	$\overline{\mathbf{A}}$										$\overline{\mathbf{A}}$	$\overline{\mathbf{Q}}$	\square	\square	\square

Note: Ticks indicate the Information Modules declared.

Manufacturing site(s)

The transport distances were adapted to the factory, specific transport distances for each provider were used for raw material transport. The manufacturing sites included in this EPD are:

Niepruszewo Ul. Modrzewiowa 2 64-320 Buk Poland

No.3 Canghai 4th Road, Yonghe Zone, Guangzhou Economic & Technological Development Zone, 511356 Guangzhou. China

No. 80 Chongqing Street, Economic & Technology Development Zone, 264006 Yantai. China

600 Conroe Park North Dr. Conroe, TX 77303 United States of America

Construction Product:

Product Description

This EPD is representative for Hempatop Finish 730.

Hempatop Finish 730 is a two-component acrylic polysiloxane topcoat. It is a glossy product with high volume solids. It has excellent gloss and colour retention on exterior exposure. The product has very good mechanical properties and chemical resistance. It does not contain isocyanates, nor does it generate di-isocyanates during welding or fire.

Hempatop Finish 730 is a high-end topcoat, suitable for a wide range of industrial structures, especially recommended for structures where long durability is required. It is intended for application on correctly prepared, primed surfaces.

Technical Information

Property	Value, Unit					
Relative density	1.429 kg/l					
Solids by volume	67%					



Property	Value, Unit				
Dry film thickness	50 micron				
Wet film thickness	73 micron				
Theoretical spreading rate	14 m²/L				
Coverage	0.102 kg/m²				

Product Contents

The material composition of the declared mixed product:

Material/Chemical Input	%
Binder	20 - 40
Filler	20 - 40
Pigments	10 - 30
Additives	< 5

Manufacturing Process

The manufacturing process for coatings involves combining and mixing multiple chemicals and materials into a homogenous product, which is then packaged and distributed.

Process flow diagram



End of Life

Coatings are typically disposed of with the substrate they are painted on. This can be through recycling, incineration or landfill, but the coating itself is unlikely to be separated from the substrate during the disposal process.



Life Cycle Assessment Calculation Rules

Declared / Functional unit description

1 kilogram of Hempatop Finish 730 coating.

System boundary

The chosen system has been Cradle to Gate with Modules C and D, which means that the Life Cycle Assessment is contemplated from the manufacturing of the paints until they leave the factory, considering the end-of-life stage and the benefits and loads beyond the system boundary.

Data sources, quality and allocation

To carry out this study, the time period January, 2023 - December, 2023 has been considered as the reference year.

The background databases are Ecoinvent v3.6 (2019) Database for the general model and CEPE Raw Material database v3.0 for raw materials.

For electricity, the consumption electricity mix from the publication "European Residual Mixes 2023" of the Association of Issuing Bodies (AIB) of Poland (0,777 kgCO2eq/kWh), and the consumption electricity mix from the publication "Ember Electricity Data Explorer - 2023" from ember-climate.org for China (1,168 kgCO2eq/kWh) and the United States of America (0,400 kgCO2eq/kWh) have been used for Hempel's manufacturing sites in Buk (Poland), Yantai (China), Guangzhou (China) and Conroe (USA), respectively.

The quality of the data and the uncertainties associated with the inventories of each input are also analysed in accordance to Table E.1 of Annex E - Schemes to be applied for data quality assessment of generic and specific data of the EN 15804:2012+A2:2019 standard.

Cut-off criteria

For the present analysis, more than 99% of the mass and energy inputs and outputs of the system have been considered, leaving out diffuse emissions in the factory and the production of manufacturing infrastructure such as industrial machinery and equipment. On the other hand, those suppliers or manufacturers of raw materials that supply less than 5% of the total raw material consumption have been omitted. The remaining suppliers have been adjusted proportionally to 100% to balance this deficit.



LCA Results

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts											
			GWP- total	GWP- fossil	GWP- biogenic	GWP- luluc	ODP	АР	EP- freshwate r		
			kg CO ₂ eq	kg CO ₂ eq	kg CO ₂ eq	kg CO ₂ eq	kg CFC11 eq	mol H ⁺ eq	kg (PO ₄) ³⁻ eq		
	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG	AGG		
Product stage	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG	AGG		
Product stage	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG	AGG		
	Total (of product stage)	A1-3	4,37E+00	4,31E+00	5,16E-02	6,16E-04	2,23E-06	2,62E-02	1,41E-04		
Construction	Transport	A4	MND	MND	MND	MND	MND	MND	MND		
process stage	Construction	A5	MND	MND	MND	MND	MND	MND	MND		
	Use	B1	MND	MND	MND	MND	MND	MND	MND		
	Maintenance	B2	MND	MND	MND	MND	MND	MND	MND		
	Repair	В3	MND	MND	MND	MND	MND	MND	MND		
Use stage	Replacement	B4	MND	MND	MND	MND	MND	MND	MND		
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND		
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND		
	Operational water use	В7	MND	MND	MND	MND	MND	MND	MND		
	Deconstruction, demolition	C1	0	0	0	0	0	0	0		
E-1-0%	Transport	C2	4,10E-03	4,09E-03	1,57E-06	4,17E-08	9,38E-10	8,30E-06	6,09E-09		
End of life	Waste processing	СЗ	0	0	0	0	0	0	0		
	Disposal	C4	1,14E-01	1,14E-01	1,17E-04	2,15E-06	9,54E-10	5,01E-05	7,31E-08		
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0	0	0	0	0	0	0		

GWP-total = Global warming potential, total; GWP-fossil = Global warming potential, fossil; GWP-biogenic = Global warming potential, biogenic; GWP-luluc = Global warming potential, land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, accumulated exceedance; and EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment



(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts											
			EP- marine	EP- terrestrial	POCP	ADP- mineral& metals	ADP- fossil	WDP	PM		
	_		kg N eq	mol N eq	kg NMVOC eq	kg Sb eq	MJ, net calorific value	m³ world eq deprived	disease incidence		
	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG	AGG		
Draduat ataga	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG	AGG		
Product stage	Manufacturing	А3	AGG	AGG	AGG	AGG	AGG	AGG	AGG		
	Total (of product stage)	A1-3	4,10E-03	4,47E-02	1,53E-02	1,18E-05	7,31E+01	3,77E+01	4,20E-07		
Construction	Transport	A4	MND	MND	MND	MND	MND	MND	MND		
process stage	Construction	A5	MND	MND	MND	MND	MND	MND	MND		
	Use	B1	MND	MND	MND	MND	MND	MND	MND		
	Maintenance	B2	MND	MND	MND	MND	MND	MND	MND		
	Repair	В3	MND	MND	MND	MND	MND	MND	MND		
Use stage	Replacement	B4	MND	MND	MND	MND	MND	MND	MND		
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND		
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND		
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND		
	Deconstruction, demolition	C1	0	0	0	0	0	0	0		
	Transport	C2	1,39E-06	1,55E-05	5,42E-06	7,50E-10	5,78E-02	3,32E-06	2,34E-10		
End of life	Waste processing	C3	0	0	0	0	0	0	0		
	Disposal	C4	2,05E-05	2,25E-04	8,75E-05	2,57E-09	7,18E-02	1,90E-04	1,23E-09		
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0	0	0	0	0	0	0		

EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment;

EP-terrestrial = Eutrophication potential, accumulated exceedance;

POCP = Formation potential of tropospheric ozone; ADP-mineral&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Depletion potential of the stratospheric ozone layer; WDP = Water (user) deprivation potential, deprivation-weighted water consumption; and $PM = Particulate\ matter.$



(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters	Parameters describing environmental impacts											
			IRP	ETP-fw	HTP-c	HTP-nc	SQP					
			kBq U ²³⁵ eq	CTUe	CTUh	CTUh	dimensionless					
	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG					
Product stage	Transport	A2	AGG	AGG	AGG	AGG	AGG					
Product stage	Manufacturing	А3	AGG	AGG	AGG	AGG	AGG					
	Total (of product stage)	A1-3	1,40E-01	8,18E+01	4,18E-09	1,67E-07	2,15E+01					
Construction	Transport	A4	MND	MND	MND	MND	MND					
process stage	Construction	A5	MND	MND	MND	MND	MND					
	Use	B1	MND	MND	MND	MND	MND					
	Maintenance	B2	MND	MND	MND	MND	MND					
	Repair	В3	MND	MND	MND	MND	MND					
Use stage	Replacement	B4	MND	MND	MND	MND	MND					
	Refurbishment	B5	MND	MND	MND	MND	MND					
	Operational energy use	B6	MND	MND	MND	MND	MND					
	Operational water use	В7	MND	MND	MND	MND	MND					
	Deconstruction, demolition	C1	0	0	0	0	0					
E 1 (1)	Transport	C2	2,52E-04	2,47E-02	3,12E-13	3,66E-11	2,11E-04					
End of life	Waste processing	С3	0	0	0	0	0					
	Disposal	C4	3,08E-04	8,13E-02	7,26E-12	8,54E-11	1,75E-01					
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0	0	0	0	0					

IRP = Potential human exposure efficiency relative to U235; ETP-fw = Potential comparative toxic unit for ecosystems; HTP-c = Potential comparative toxic unit for humans; HTP-nc = Potential comparative toxic unit for humans; and SQP = Potential soil quality index.



(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

			DEDE	DEDM	DEDT	DENDE	DENIDA4	DENDT
			PERE	PERM	PERT	PENRE	PENRM	PENRT
			MJ	MJ	MJ	MJ	MJ	MJ
	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG
Decide et ataux	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG
Product stage	Manufacturing	А3	AGG	AGG	AGG	AGG	AGG	AGG
	Total (of product stage)	A1-3	6,95E+00	1,25E-02	6,97E+00	7,85E+01	6,39E-01	7,92E+01
Construction	Transport	A4	MND	MND	MND	MND	MND	MND
process stage	Construction	A5	MND	MND	MND	MND	MND	MND
	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND
	Repair	В3	MND	MND	MND	MND	MND	MND
Jse stage	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
	Deconstruction, demolition	C1	0	0	0	0	0	0
ما ما الله	Transport	C2	7,55E-05	0	7,55E-05	6,14E-02	0	6,14E-02
end of life	Waste processing	СЗ	0	0	0	0	0	0
	Disposal	C4	1,73E-03	0	1,73E-03	7,62E-02	0	7,62E-02
otential enefits and ads beyond ne system oundaries	Reuse, recovery, recycling potential	D	0	0	0	0	0	0

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;
PERM = Use of renewable primary energy resources used as raw

materials;

PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding nonrenewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials;

PENRT = Total use of non-renewable primary energy resource



(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing resource use, secondary materials and fuels, use of water										
			SM	RSF	NRSF	FW				
			kg	MJ net calorific value	MJ net calorific value	m³				
	Raw material supply	A1	AGG	AGG	AGG	AGG				
Droduct stage	Transport	A2	AGG	AGG	AGG	AGG				
Product stage	Manufacturing	А3	AGG	AGG	AGG	AGG				
	Total (of product stage)	A1-3	0	0	0	8,72E-01				
Construction	Transport	A4	MND	MND	MND	MND				
process stage	Construction	A5	MND	MND	MND	MND				
	Use	B1	MND	MND	MND	MND				
	Maintenance	B2	MND	MND	MND	MND				
	Repair	ВЗ	MND	MND	MND	MND				
Use stage	Replacement	B4	MND	MND	MND	MND				
	Refurbishment	B5	MND	MND	MND	MND				
	Operational energy use	B6	MND	MND	MND	MND				
	Operational water use	B7	MND	MND	MND	MND				
	Deconstruction, demolition	C1	0	0	0	0				
End of life	Transport	C2	0	0	0	7,18E-07				
End of life	Waste processing	СЗ	0	0	0	0				
	Disposal	C4	0	0	0	9,01E-06				
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0	0	0	0				

SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water



(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Other environmental information describing waste categories										
			HWD	NHWD	RWD					
			kg	kg	kg					
	Raw material supply	A1	AGG	AGG	AGG					
Decide at a tage	Transport	A2	AGG	AGG	AGG					
Product stage	Manufacturing	А3	AGG	AGG	AGG					
	Total (of product stage)	A1-3	1,41E-04	1,95E-01	1,13E-04					
Construction	Transport	A4	MND	MND	MND					
process stage	Construction	A5	MND	MND	MND					
	Use	B1	MND	MND	MND					
	Maintenance	B2	MND	MND	MND					
	Repair	В3	MND	MND	MND					
Use stage	Replacement	B4	MND	MND	MND					
	Refurbishment	B5	MND	MND	MND					
	Operational energy use	В6	MND	MND	MND					
	Operational water use	В7	MND	MND	MND					
	Deconstructio n, demolition	C1	0	0	0					
End of W	Transport	C2	1,55E-07	9,45E-06	4,15E-07					
End of life	Waste processing	СЗ	0	0	0					
	Disposal	C4	1,51E-07	1,00E+00	4,46E-07					
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0	0	0					

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed



(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Other environmental information describing output flows – at end of life											
			CRU	MFR	MER	EE	Biogenic carbon (product)	Biogenic carbon (packaging)			
			kg	kg	kg	MJ per energy carrier	kg C	kg C			
	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG			
Product stage	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG			
	Manufacturing	А3	AGG	AGG	AGG	AGG	AGG	AGG			
	Total (of product stage)	A1 -3	3,90E-03	6,53E-03	8,31E-03	5,52E-02	0	0			
Construction	Transport	A4	MND	MND	MND	MND	MND	MND			
process stage	Construction	A5	MND	MND	MND	MND	MND	MND			
	Use	B1	MND	MND	MND	MND	MND	MND			
	Maintenance	B2	MND	MND	MND	MND	MND	MND			
	Repair	В3	MND	MND	MND	MND	MND	MND			
Use stage	Replacement	B4	MND	MND	MND	MND	MND	MND			
	Refurbishment	B5	MND	MND	MND	MND	MND	MND			
	Operational energy use	В6	MND	MND	MND	MND	MND	MND			
	Operational water use	В7	MND	MND	MND	MND	MND	MND			
	Deconstructio n, demolition	C1	0	0	0	0	0	0			
	Transport	C2	0	0	0	0	0	0			
End of life	Waste processing	СЗ	0	0	0	0	0	0			
	Disposal	C4	0	0	0	0	0	0			
Potential benefits and loads beyond the system	Reuse, recovery, recycling potential	D	0	0	0	0	0	0			

CRU = Components for reuse; MFR = Materials for recycling MER = Materials for energy recovery; EE = Exported Energy



Scenarios and additional technical information

Scenarios and additional technical information			
Scenario	Parameter	Units	Results
A4 – Transport to the building site	Module not declared		
A5 – Installation in the building	Module not declared		
B2 – Maintenance	Module not declared		
B3 – Repair	Module not declared		
B4 – Replacement	Module not declared		
B5 – Refurbishment	Module not declared		
Reference service life	Module not declared		
B6 – Use of energy; B7 – Use of water	Module not declared		
C1 to C4 End of life,	Waste for final disposal: Landfill	%	100
	Transport to waste processing: Truck, fuel consumption	kgkm	3.66E-05
	Transport to waste processing: Distance	km	30
	Transport to waste processing: Capacity utilisation	%	85
Module D	Module declared		



Interpretation

The results displayed in Figure 1 apply to 1 kilogram of Hempatop Finish 730 coating. It illustrates the relative contributions of the different modules assessed to various environmental impact categories and to primary energy use. Most impacts relate to the raw materials that compose the coating (included in Module A1-A3).




Figure 1: Relative contribution of each module for 1 kilogram of Hempatop Finish 730 coating.

Raw material manufacturing and transport (79,95%), packaging (18,57%) and consumption (1,49%) account for the total of the use of renewable primary energy resources (PERT). The manufacturing of raw materials and its transport (90,49%) has the greatest impact on the use of non-renewable primary energy resources (PENRT), while the impact of the production process (due to plant consumption and product packaging) measures 9,51%. The pre-product manufacturing (raw materials and its distribution) is the main contributor in all impact categories for Module A1-A3 with an average of 87,18%.

GWP-biogenic indicator emissions are majorly caused by raw material's packaging, which its waste management is done in A1-A3 modules (fabrication stage). This clarifies the reason why biogenic emissions does not follow "-1+1" biogenic CO2 sequestration flow, as the product by itself has not biogenic carbon content.



References

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A2:2019. London, BSI, 2019.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.

Ecoinvent Version 3.6: Database for Life Cycle Assessment. Swiss Centre for Life Cycle Inventories (Ecoinvent Centre), 2019.

CEPE Raw Material database v3.0: Raw materials LCI database for the European coatings and printing ink industries. The European Council of the Paint, Printing Ink, and Artist's Colours Industry (CEPE), 2016.

Life Cycle Assessment: Hempatop Finish 730 coating. LCA report by The Catalonia Institute of Construction Technology (ITeC), 2024.