



Statement of Verification

BREG EN EPD No: 000775

Issue: 01

This is to verify that the Environmental Product Declaration provided by:

Hambleside Danelaw Ltd

are in accordance with the requirements of:

EN 15804:2012+A2:2019

and


BRE Global Scheme Document SD207

This declaration is for:

1 linear metre of built up (Site Assembled) Zenon PB-02 panel rooflight weighing 6.2 kg

Company Address

Hambleside Danelaw Ltd.
Long March
Daventry
Northamptonshire
NN11 4NR



Hambleside Danelaw
Building Products



Signed for BRE Global Limited

Hayley Thomson

Operator

13 March 2026

Date of this Issue

13 March 2026

Date of First Issue

12 March 2031

Expiry Date



This Statement of Verification is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this statement of verification please, visit www.greenbooklive.com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: Enquiries@breglobal.com





Environmental Product Declaration

EPD Number: 000775

General Information

EPD Programme Operator	Applicable Product Category Rules
BRE Global Watford, Herts WD25 9XX United Kingdom	BRE 2025 Product Category Rules (PN 514 Rev 3.2) for Type III environmental product declaration of construction products to EN 15804:2012+A2:2019
Commissioner of LCA study	LCA consultant/Tool
Hambleside Danelaw Ltd. Long March Daventry Northamptonshire NN11 4NR	BRE LINA A2
Declared/Functional Unit	Applicability/Coverage
1 linear metre of built up (Site Assembled) Zenon PB-02 panel rooflight weighing 6.2 kg.	Product Specific
EPD Type	Background database
Cradle to Gate with options	Ecoinvent 3.8
Demonstration of Verification	
CEN standard EN 15804 serves as the core PCR ^a	
Independent verification of the declaration and data according to EN ISO 14025:2010 <input checked="" type="checkbox"/> Internal <input type="checkbox"/> External	
(Where appropriate ^b)Third party verifier: Kim Allbury	
a: Product category rules b: Optional for business-to-business communication; mandatory for business-to-consumer communication (see EN ISO 14025:2010, 9.4)	
Comparability	
Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A2:2019. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A2:2019 for further guidance	



Information modules covered

Product			Construction		Use stage							End-of-life				Benefits and loads beyond the system boundary
A1	A2	A3	A4	A5	Related to the building fabric					Related to the building		C1	C2	C3	C4	D
Raw materials supply	Transport	Manufacturing	Transport to site	Construction – Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, Recovery and/or Recycling potential
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>								

Note: Ticks indicate the Information Modules declared.

Manufacturing site(s)

Hambleside Danelaw Ltd.
Long March
Daventry
Northamptonshire
NN11 4NR

Construction Product:

Product Description

Zenon in-plane built-up panel rooflights, also referred to as site assembled insulated rooflights are profiled, triple skin, translucent GRP products, comprising of a weather sheet, liner panel, and a layer of insulation. Manufactured in various fire ratings and thermal performances to suit the building's specification requirements. They are typically 1000mm cover width and are profiled to match the major UK metal profile manufacturers. The design and width are the same across the system and the length will be varied according to projects. Therefore, the LCA analysis was conducted for 1 linear meter, which allows the end user to scale the LCA results for different lengths.


Technical Information

Property	Value, Unit
Material	Glass Reinforced Polyester (GRP) to BS EN 1013:2012+A1:2014 (UK Annex)
Insulant	10mm insulation
Profile	To match profiled metal system with 0.7mm rigid liner
Length	To suit application
Cover Width	To match profiled metal system
Finish	Natural Translucent



Property	Value, Unit
Fire Properties	Outer: External Fire Exposure BROOF(t4) to BS EN 13501-5 Liner: Class 1 to BS476-7, TP(a) rigid to BS 2782-0, Method 508A
End Lap Lengths	150mm with the fixings at the centre of the lap
L-Solar	43%
T-Solar	46%
U Value	1.3 W/m ² K
Non-Fragility Classification	Class B
Additional Information	Manufactured using UV stabilised resins and Zenon Shield surface protection. UKCA and CE marked in accordance with BS EN 1013:2012+A1:2014 (UK Annex). Performance data obtained through physical testing programme at National Physical Laboratory

Note: The technical information is gathered from the product specification document, please contact Hambleside Danelaw for details. For full installation details including liner and insulant, please refer to manufacturer's installation recommendations.




Main Product Contents

Material/Chemical Input	%
Resin	51.11
Glass	25.56
Scrim	0.24
Minor chemicals	0.8
Film	2.17
Insulation	20.12

Manufacturing Process

A controlled combination of raw materials, including resin and glass rovings are laid down on to a flat carrier film. This combination is then formed into the profile required and heated until it has cured. The cured profile shape is then trimmed to the length and width required against the customer's order. The finished product is then packaged and shipped to the customer.

Process flow diagram



Construction Installation

1. Rooflight Outer Sheet

GRP (Glass Reinforced Polyester) rooflight outer sheets available in a wide variety of profiles to match the surrounding metal cladding, different specifications and weights to meet all customer requirements.

2. Rooflight Liner Sheet

GRP rooflight liner sheets available in a wide variety of profiles to match the surrounding roof liner panels, different specifications and weights to meet all customer requirements.

3. Sealing Strip Liner Panel

A 50x1mm polyband type tape should be positioned half onto the rooflight and half onto the metal liner panel along the side laps. The end laps of the liner panels should be sealed with one row of 6x5mm, 6mm Ø or 8mm Ø bead butyl type strip sealant.



4. Intermediate Layer

The polycarbonate intermediate insulation layer may be secured in place using the Polyband type sidelap tape around the perimeter of the panels and across end butt joint where this coincides with a purlin position. Alternatively, a butyl strip sealant may be used between the insulation layer and roof liner system.

5. Primary Fixings

The purpose of primary fixings is to secure the rooflight outer sheet in position. They must also create sufficient compression of the sealant strips to provide a continuous weather seal across the width of the profile. Differences in the design and shape of profiles means the number and position of fixings required to achieve a complete seal may vary. There should always be a minimum of 5 fixings per purlin and each should have a minimum 29mm diameter self-sealing washer with a poppy red cap. Ideally, the fixings should be positioned as evenly as possible across the profile of the sheet and central to each trough. Wider troughs may need two each.

6. Side Stitch Fastener

A sidelap stitch fastener is used when fixing the rooflight sidelaps over the metal profile. These fixings should have a poppy red cap and use a minimum of a 16mm diameter self-sealing washer and be placed at a maximum of 400mm centres.

7. Expanding Grommet Fastener

When the metal cladding is fitted over the GRP, an expanding grommet type fastener to suit durability requirements should be used to fasten the side lap of the metal over the rooflight. Where non-fragile performance is required, these should be metal Fab-Lok or similar types.

8. Sidelap Sealant

The sidelap sealant is essential and must be installed on the crown of the underlapping panel. The sealant should be a continuous 6x5mm butyl type strip.

9. End Lap Sealant

The sealant strips should be 6x5mm, 6mm Ø or 8mm Ø bead butyl type strip sealant. Two strips should be positioned approximately 10 to 15mm either side of the fixing, and a further strip positioned 15mm from the outer end lap. Where a better seal is required at the bottom of the lap to keep out dirt and trapped water, a bead of premium quality neutral cure silicone sealant positioned approximately 10 to 15mm from the bottom of the lap may be used.

Alternatively, and for improved sealing, the sealing strip on the line of the fixings can be a single 18x4mm or 22x5mm U-section butyl type strip sealant with a 6x5mm, 6mm Ø or 8mm Ø bead placed 15mm from the end of each sheet as illustrated.

Use Information

Maintenance - Clean periodically with warm water and soap solution, avoid harsh detergents. Remove persistent stains by rubbing with a bristle brush. Remove tar and grease with white spirit.

Repairs - Dependent upon condition. Repairs sometimes possible; seek advice from Technical Department.

End of Life

At the end of life, the product can be disposed of via landfill or alternatively can be sent to an Energy from waste (EFW) plant where it is converted to SRF (Solid Recovery Fuel). Following this sophisticated SRF manufacturing process, the end product produced is a resource from which energy can be harnessed. It is used in cement kilns, paper mills and power stations as an alternative to fossil fuels. However, as the end-of-life options are site dependent, industrial average end-of-life data has been used for this EPD according BRE PCR for Type III EPD of Construction Products to EN 15804+A2, i.e. 100% GRP and insulation waste are incinerated.



Life Cycle Assessment Calculation Rules

Declared / Functional unit description

1 linear metre of built up (Site Assembled) Zenon PB-02 panel rooflight weighing 6.2 kg.

System boundary

This is a Cradle-to-Gate with Module C & D and options LCA, reporting all production life cycle stages of modules A1 to A3, construction stages A4, A5 and end-of-life stages C1-C4, and D in accordance with EN 15804:2012+A2:2019 and BRE 2025 Product Category Rules (PN 514 Rev 3.2). The intended purpose of this LCA is for the data and results to be used in a published third-party verified EPD.

Data sources, quality and allocation

Specific primary data derived from Hambleside Danelaw’s production process at Long March, Daventry, Northamptonshire NN11 4NR factory, have been modelled using the LINA LCA A2 software A2 and the ecoinvent 3.8 database. In accordance with the requirements of EN 15804:2012+A2:2019, the most current available data has been used. The manufacturer-specific data from Hambleside-Danelaw covers a period of one year (01/01/2022 – 31/12/2022). Secondary data has been obtained for all other upstream and downstream processes that are beyond the control of the manufacturer (i.e. raw material production) from the ecoinvent 3.8 database. All ecoinvent datasets are complete within the context used and conform to the system boundary and the criteria for the exclusion of inputs and outputs, according to the requirements specified in EN 15804:2012+A2:2019.

The LCA study is for Zenon PB-02 product and the factory also produces other products. All energy, water and waste have been allocated to the product by linear metre according to the provisions of the BRE PCR PN514 Rev 3.2 and EN 15804:2012+A2:2019. Site wide values for energy, water and wastewater have been taken from bills. Figures for the raw materials, ancillary materials and packaging were from actual usages.

Quality Level	Geographical representativeness	Technical representativeness	Time representativeness
Very Good	Data from area under study.	Data from processes and products under study. Same state of technology applied as defined in goal and scope (i.e. identical technology).	There is less than 5 years between the ecoinvent LCI reference year, and the time period for which the LCA was undertaken.

Specific UK datasets have been selected from the ecoinvent LCI for this LCA. The quality level of geographical and technical representativeness is therefore very good. The quality level of time representativeness is very good as the background LCI datasets are based on ecoinvent v3.8 which was compiled in 2021. Therefore, there is less than 5 years between the ecoinvent LCI reference year and the time period for which the LCA was undertaken.

Location-based approach has been used for electricity modelling.

UK Consumption mix was used for electricity with an emissions factor of 0.239kgCO₂e/kWh.

UK Natural gas data (at industrial furnace) was used with an emissions factor of 0.232 kgCO₂eq/kWh.

UK renewable electricity (roof, mono solar PV) was used with an emission factor of 0.125 kgCO₂e/kWh.

Cut-off criteria

All processes associated with the manufacturing process have been included. All inputs or outputs have been included and all raw materials, packaging and transport, energy, water use, emissions, and wastes, are included, except for direct emissions to water and soil, which are not measured. Upstream extraction and/or processing of inputs are included within the use of the background datasets within LINA. There is no



information about the chemical composition of accelerator and catalyst input materials. Therefore, a default ecoinvent dataset - 'unspecified organic chemical' has been used as a proxy for the accelerator and catalyst.



LCA Results

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			GWP-total	GWP-fossil	GWP-biogenic	GWP-luluc	ODP	AP	EP-freshwater
			kg CO ₂ eq	kg CFC11 eq	mol H ⁺ eq	kg (PO ₄) ³⁻ eq			
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	3.59E+01	3.63E+01	-4.36E-01	1.56E-02	2.47E-06	1.48E-01	5.70E-03
Construction process stage	Transport	A4	2.16E-01	2.15E-01	1.84E-04	8.46E-05	4.98E-08	8.74E-04	1.39E-05
	Construction	A5	3.47E+00	2.32E+00	9.15E-01	2.32E-01	2.96E-07	1.22E-02	2.15E-03
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
100% GRP and insulation waste to incineration Scenario									
End of life	Deconstruction, demolition	C1	1.07E-01	1.07E-01	7.15E-05	1.19E-05	3.26E-09	9.55E-05	1.70E-06
	Transport	C2	3.10E-02	3.09E-02	2.64E-05	1.21E-05	7.15E-09	1.25E-04	1.99E-06
	Waste processing	C3	1.48E+01	1.48E+01	1.39E-03	1.25E-04	3.24E-08	3.41E-03	4.39E-05
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-5.44E+00	-5.35E+00	-7.67E-02	-6.10E-03	-3.71E-07	-3.10E-02	-3.10E-03

GWP-total = Global warming potential, total;
 GWP-fossil = Global warming potential, fossil;
 GWP-biogenic = Global warming potential, biogenic;
 GWP-luluc = Global warming potential, land use and land use change;

ODP = Depletion potential of the stratospheric ozone layer;
 AP = Acidification potential, accumulated exceedance; and
 EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment



LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			EP-marine	EP-terrestrial	POCP	ADP-mineral&metals	ADP-fossil	WDP	PM
			kg N eq	mol N eq	kg NMVOC eq	kg Sb eq	MJ, net calorific value	m ³ world eq deprived	disease incidence
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	2.60E-02	2.75E-01	1.04E-01	2.38E-04	5.45E+02	1.80E+01	2.25E-06
Construction process stage	Transport	A4	2.63E-04	2.88E-03	8.81E-04	7.49E-07	3.26E+00	1.47E-02	1.86E-08
	Construction	A5	4.38E-03	2.61E-02	9.20E-03	3.10E-05	4.87E+01	2.87E+00	1.34E-07
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
100% GRP and insulation waste to incineration Scenario									
End of life	Deconstruction, demolition	C1	1.93E-03	3.48E-04	1.22E-04	3.71E-08	2.61E-01	1.12E-02	1.81E-09
	Transport	C2	3.78E-05	4.13E-04	1.26E-04	1.07E-07	4.67E-01	2.10E-03	2.67E-09
	Waste processing	C3	1.92E-03	1.63E-02	3.97E-03	1.05E-06	2.76E+00	9.35E-01	1.66E-08
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-4.57E-03	-4.50E-02	-1.26E-02	-3.30E-06	-8.64E+01	-2.35E+00	-2.09E-07

EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment;
 EP-terrestrial = Eutrophication potential, accumulated exceedance;
 POCP = Formation potential of tropospheric ozone;
 ADP-mineral&metals = Abiotic depletion potential for non-fossil resources;

ADP-fossil = Depletion potential of the stratospheric ozone layer;
 WDP = Water (user) deprivation potential, deprivation-weighted water consumption; and
 PM = Particulate matter.



LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

			IRP	ETP-fw	HTP-c	HTP-nc	SQP
			kBq U ²³⁵ eq	CTUe	CTUh	CTUh	dimensionless
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	1.96E+00	8.49E+02	2.05E-08	9.76E-07	1.16E+02
Construction process stage	Transport	A4	1.67E-02	2.54E+00	8.23E-11	2.66E-09	2.24E+00
	Construction	A5	2.88E-01	6.73E+01	3.80E-09	4.65E-08	2.22E+01
Use stage	Use	B1	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND
100% GRP and insulation waste to incineration Scenario							
End of life	Deconstruction, demolition	C1	1.47E-03	4.99E-01	8.18E-12	2.16E-10	5.84E-01
	Transport	C2	2.40E-03	3.65E-01	1.18E-11	3.82E-10	3.21E-01
	Waste processing	C3	8.43E-03	3.09E+01	1.32E-09	5.01E-08	9.21E-01
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-1.48E+00	-7.60E+01	-1.28E-09	-4.02E-08	-2.51E+01

IRP = Potential human exposure efficiency relative to U235;
ETP-fw = Potential comparative toxic unit for ecosystems;
HTP-c = Potential comparative toxic unit for humans;

HTP-nc = Potential comparative toxic unit for humans; and
SQP = Potential soil quality index.



LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

			PERE	PERM	PERT	PENRE	PENRM	PENRT
			MJ	MJ	MJ	MJ	MJ	MJ
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	2.31E+01	7.45E+00	3.06E+01	4.21E+02	1.22E+02	5.42E+02
Construction process stage	Transport	A4	4.59E-02	0.00E+00	4.59E-02	3.20E+00	0.00E+00	3.20E+00
	Construction	A5	7.41E-01	8.47E+00	9.21E+00	1.92E+01	2.30E+01	4.22E+01
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
100% GRP and insulation waste to incineration Scenario								
End of life	Deconstruction, demolition	C1	6.67E-03	0.00E+00	6.67E-03	-2.75E+01	2.77E+01	2.59E-01
	Transport	C2	6.58E-03	0.00E+00	6.58E-03	4.59E-01	0.00E+00	4.59E-01
	Waste processing	C3	1.07E-01	0.00E+00	1.07E-01	-1.88E+02	1.91E+02	2.74E+00
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-1.30E+01	0.00E+00	-1.30E+01	-8.69E+01	0.00E+00	-8.69E+01

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;
 PERM = Use of renewable primary energy resources used as raw materials;
 PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;
 PENRM = Use of non-renewable primary energy resources used as raw materials;
 PENRT = Total use of non-renewable primary energy resource



LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

			SM	RSF	NRSF	FW
			kg	MJ net calorific value	MJ net calorific value	m ³
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	7.09E-02	2.86E-06	0.00E+00	4.26E-01
Construction process stage	Transport	A4	0.00E+00	0.00E+00	0.00E+00	3.63E-04
	Construction	A5	3.51E-02	6.38E-09	0.00E+00	6.78E-02
Use stage	Use	B1	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND
100% GRP and insulation waste to incineration Scenario						
End of life	Deconstruction, demolition	C1	8.08E-05	6.39E-09	0.00E+00	2.65E-04
	Transport	C2	0.00E+00	0.00E+00	0.00E+00	5.21E-05
	Waste processing	C3	0.00E+00	0.00E+00	0.00E+00	2.18E-02
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	-5.86E-02

SM = Use of secondary material;
RSF = Use of renewable secondary fuels;

NRSF = Use of non-renewable secondary fuels;
FW = Net use of fresh water



LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Other environmental information describing waste categories			HWD	NHWD	RWD
			kg	kg	kg
Product stage	Raw material supply	A1	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	1.17E+00	2.67E+01	7.12E-04
Construction process stage	Transport	A4	3.59E-03	6.38E-02	2.20E-05
	Construction	A5	2.37E-01	4.74E+00	1.32E-04
Use stage	Use	B1	MND	MND	MND
	Maintenance	B2	MND	MND	MND
	Repair	B3	MND	MND	MND
	Replacement	B4	MND	MND	MND
	Refurbishment	B5	MND	MND	MND
	Operational energy use	B6	MND	MND	MND
	Operational water use	B7	MND	MND	MND
100% GRP and insulation waste to incineration Scenario					
End of life	Deconstruction, demolition	C1	5.19E-04	9.10E-01	1.57E-06
	Transport	C2	5.15E-04	9.15E-03	3.16E-06
	Waste processing	C3	2.26E-01	6.51E+00	6.26E-06
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-3.50E-01	-1.89E+01	-4.43E-04

HWD = Hazardous waste disposed;
 NHWD = Non-hazardous waste disposed;
 RWD = Radioactive waste disposed



LCA Results (continued)

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Other environmental information describing output flows – at end of life								
			CRU	MFR	MER	EE	Biogenic carbon (product)	Biogenic carbon (packaging)
			kg	kg	kg	MJ per energy carrier	kg C	kg C
Product stage	Raw material supply	A1	AGG	AGG	AGG	AGG	AGG	AGG
	Transport	A2	AGG	AGG	AGG	AGG	AGG	AGG
	Manufacturing	A3	AGG	AGG	AGG	AGG	AGG	AGG
	Total (Consumption grid)	A1-3	0.00E+00	8.60E-02	3.25E-01	2.30E-03	0.00E+00	2.12E-01
Construction process stage	Transport	A4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Construction	A5	0.00E+00	1.11E-07	4.72E-11	5.09E-06	4.52E-02	0.00E+00
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	MND	MND	MND	MND	MND	MND
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
100% GRP and insulation waste to incineration Scenario								
End of life	Deconstruction, demolition	C1	0.00E+00	1.11E-07	4.72E-11	5.09E-06	0.00E+00	0.00E+00
	Transport	C2	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Waste processing	C3	0.00E+00	0.00E+00	0.00E+00	7.02E+01	0.00E+00	0.00E+00
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

CRU = Components for reuse;
MFR = Materials for recycling

MER = Materials for energy recovery;
EE = Exported Energy



Scenarios and additional technical information

Scenarios and additional technical information			
Scenario	Parameter	Units	Results
A4 – Transport to the building site	Based on a typical delivery trip Daventry to Manchester		
	Fuel type / Vehicle type	Litre of fuel type per distance or vehicle type	Road Transport via 16-32 ton lorry
	Distance:	km	209
A5 – Installation in the building	Product is lifted onto the roof and fixed in place. Assumed local materials sourced from 30km delivered from 31 t lorry.		
	Sealant Tube	kg	0.1
	Sealant Tape	kg	0.9
	Screws	kg	0.15
	Electricity for Drill	kWh	0.001169
	Deisel	kg	0.000024
	Crane Exhaust Emissions	kg	0.000024
	Wooden pallet waste to recycling	kg	0.494
	Cover Sheets (GRP) waste to landfill	kg	0.03804
	Cover Sheet (PC) waste to landfill	kg	0.00307
	Polythene Wrap waste to landfill	kg	0.1168
Sealant Tube – to landfill	kg	0.1	
C1 to C4 End of life,			
C1 – Deconstruction	It has been assumed that the product will be dismantled at the building's end of service life, where a crane will be used to bulldoze the building.		
	Transport of Diesel	km	30
	Electricity Use - Drill Battery	kWh	0.001169
	Deisel	kg	0.000024
	Tape – to landfill	kg	0.9
	Screws – to landfill	kg	0.15



Scenarios and additional technical information

Scenario	Parameter	Units	Results
C2 – Transport from site to pre-processing facility or landfill	A 30km assumption has been used in this module. The EPD users can calculate the C2 impacts for a specific distance on this basis.		
	Road, 16-32 metric ton, euro5	km	30
C3 - Pre-processing of uninstalled product	The end-of-waste state has been assumed when the waste flow is incinerated (energy recovery from waste, assuming the plant has an R1 value > 0.6).		
	There is currently no process in place to dispose of the product waste. Therefore, industrial average end-of-life data for 'Cladding panel, glass reinforced plastic (GRP) has been used according to BRE PCR PN 514 Rev 3.2, i.e. 100% of waste to incineration. So all 6.2kg of product waste will be incinerated.		
	Waste to Incineration (plastic)	kg	6.2
C4 – Disposal	Industrial average end-of-life data for 'Cladding panel, glass reinforced plastic (GRP) has been used according to BRE PCR PN 514 Rev 3.1, i.e. 100% of waste to incineration. Therefore, no waste is sent to landfill.		
Module D	The existing recycled content is less than 1%, so 6.2kg plastic waste is declared in Module D for energy recovery benefits. As there is a lack of GRP incineration data, Incineration of plastic mixture waste dataset is used as a proxy to calculate the benefits in Module D, therefore, a specific calorific value for incineration is unable to be provided. But the electricity benefit realised from the incineration process is 3.66MJ/kg, the heat benefit realised from the incineration process is 7.66MJ/kg.		
	For benefits due to incineration of GRP waste, the EU electricity (Electricity, high voltage (RER) market group for electricity, high voltage, 2021) with an emission factor of 0.396kgCO ₂ eq/kWh, EU heat (Heat, district or industrial, natural gas (RER) market for heat, district or industrial, natural gas, 2021) with an emission factor of 0.187kgCO ₂ eq/kWh, and EU heat (Heat, district or industrial, other than natural gas (RER) market for heat, district or industrial, other than natural gas, 2021) with an emission factor of 0.244kgCO ₂ eq/kWh have been used as the background data for the energy recovered.		
	Benefits due to incineration of plastic mixture	kg	6.2

Interpretation

Out of the total mass of input materials, resin accounts for 51.11%, glass fibres account for 25.56%, insulation accounts for 20.12%, films account for 2.17% and other materials account for the remaining 1.04%. The bulk of the environmental impacts and primary energy demand are attributed to the manufacturing phase, covered by information modules A1-A3 of EN15804:2012+A2:2019.

As a result, polyester resin and GCP waste treatment contribute the most on GWP and overall environmental impacts.




Figure 1



References

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A2:2019. London, BSI, 2019.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.

BSI. Light transmitting single skin profiled plastics sheets for internal and external roofs, walls and ceilings. Requirements and test methods. BS EN 1013:2012+A1:2014. London, BSI, 2013.

BSI. Fire classification of construction products and building elements. Classification using data from external fire exposure to roofs tests. BS EN 13501-5:2016. London, BSI, 2016.

BSI. Fire tests on building materials and structures. Method of test to determine the classification of the surface spread of flame of products. BS 476-7:1997. London, BSI, 1997.

BSI. Methods of testing plastic – Introduction. BS 2782-0:2011. London, BSI, 2011.